

**Premium absolute solid shaft encoder**

- 99,5mm diameter
- Extremely robust design
- Shock and vibration protected
- Inductive scanning

**Encoder configuration**

Type	PSE
Model	903
Shaft type	Ø14 mm with key nut
Flange type	Euro-flange (B10-type)
Output interface	EtherCAT®
Absolute resolution	19 bit singleturn
Connection type	3xM12 connectors
Connecting direction	Radial

Mechanical data

Operating temperature	-20 °C...+85 °C
Ingress protection class [IEC 60529]	IP67/IP66 (Encoder body/Shaft inlet)
Vibration [IEC 60068-2-6]	≤ 200 m/s ²
Shock [IEC 60068-2-27]	≤ 1500 m/s ²
Shaft load (axial/radial)	210 N / 280 N
Rotational speed max	6000 rpm
Shaft material	Stainless steel with insulated peek insert
Cover material	Aluminium (anodized)
Weight	1700 g

Electrical data

Polarity protected	Yes
Current consumption	100 mA at 24 Vdc
Absolute accuracy	± 100 arcsec
Supported profile	CIA DS-406 v.4.0
Baud rate	100 Mbit/s
Cycle time	32.5 us...32 ms, Distributed Clocks (DC)
Power supply	9...36 Vdc

Supported functions


Preset, Scaling, Code sequence, Velocity, Acceleration, FoE
(File over EtherCAT)

Pin Configuration


Function	Pin
----------	-----

M12 4p D-coded (Out)


Tx+	1
Rx+	2
Tx-	3
Rx-	4

**M12 4p D-coded (IN)**

Tx+	1
Rx+	2
Tx-	3
Rx-	4

**M12 4p A-coded (Supply)**

+E Volt	1
0 Volt	3



Order information

Part number

1130831-01